

## Goodyear Lubricants

420 Imperial Court Bensalem, PA 19020

United States Tel: (215) 244-2114

Fax: (215) 244-2118

[www.gylubricants.com](http://www.gylubricants.com)



# PERFORMANCE MAX FULL SYNTHETIC HEAVY DUTY MV ATF

## OVERVIEW

**Performance Max FULL SYNTHETIC HEAVY DUTY MV ATF** is a top-tier, fully synthetic transmission fluid designed for use in a wide variety of heavy duty automatic transmissions. Formulated to meet the requirements of modern heavy-duty automatic transmission, **Performance Max FULL SYNTHETIC HEAVY DUTY MV ATF** offers excellent shifting and power transfer performance and true wide-temperature operation.

## FEATURES & BENEFITS

**Performance Max FULL SYNTHETIC HEAVY DUTY MV ATF** has excellent frictional properties that ensure smooth shifting and power transfer in all operating conditions. Its fully synthetic base stocks provide outstanding start up circulation and exceptional low and high temperature characteristics and it is specifically designed for heavy duty transmissions.

## APPLICATIONS

**Performance Max FULL SYNTHETIC HEAVY DUTY MV ATF** is specifically designed for use in heavy-duty automatic transmissions but can be used in other higher viscosity ATF applications. This high-performance product is intended for severe duty, high temperatures, and heavy loads.

## SPECIFICATIONS

Allison C4, TES-295 • BMW LT 71141; 2634; ETL-7045E; -8072B • Chrysler +3; +4 • Ford M; MV • GM III(H) • HMC / KIA SP-II; SP-III • Honda ATF Z1 • Jaguar Idemitsu K17 • JASO M315-2004 • Land Rover Texaco N402 • MAN 339 V1; 339 Z2 • Mazda ATF M-III; ATF M-V • Mercedes 236.5; 6;.7; 236.9 ; 10; 11; ATF 3403 M-115 • Nissan Matic J; Matic K • Subaru ATF, ATF-HP • Toyota T-III; T-IV; JWS 3309 • Voith H55.6335.XX (G607) • VW/Audi G 052 025 (09M); G 052 990 (09A) • ZF TE-ML 03D; 04D; 14A; 14B; 16L; 17C

\*OEM approved fluids are required for vehicle warranty maintenance in most instances.

## TYPICAL PROPERTIES

| Product Code            | ATF-PM-SB-TES-295 |
|-------------------------|-------------------|
| Viscosity, cSt @ 40 °C  | 37.91             |
| Viscosity, cSt @ 100 °C | 7.0               |
| Viscosity, cP @ -40°C   | 19,500            |
| Viscosity Index         | 150               |
| Flash Point, °F         | 213               |
| Pour Point, ° F         | -42               |