

Goodyear Lubricants

420 Imperial Court Bensalem, PA 19020

United States Tel: (215) 244-2114

Fax: (215) 244-2118

www.gylubricants.com



PERFORMANCE MAX SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS

OVERVIEW

Performance Max SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS are designed to meet the high standards of lubrication for modern naturally aspirated, turbo-charged and super-charged engines. Designed for the latest high-performance European gasoline and diesel engines, **Performance Max SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS** products maintain extended drain intervals and enhanced fuel economy, while providing superior oxidation protection, and low temperature flow properties.

FEATURES & BENEFITS

Performance Max SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS engine oil products provide superior engine wear protection by inhibiting the formation of sludge and varnish as well as rust and bearing corrosion. **Performance Max SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS** engine oil products use synthetic base stocks and advanced additive systems and have excellent viscosity and thermal breakdown properties at higher temperatures, while still providing protection during cold starts. They are low volatility oils leading to reduced oil consumption.

APPLICATIONS

Performance Max SYN EURO SERIES FULL SYN PASSENGER CAR ENGINE OILS engine oil products are "full SAPS" lubricants with excellent TBN retention and viscosity increase control essential for extended drain applications. Their unique formulation protects gasoline and diesel engines designed for extended service ranges or higher performance. The high level of alkalinity in these oils provides long-lasting and effective protection from the effects of acidic compounds formed due to the combustion process, as it is designed to deplete slowly over its service life. This ensures high levels of engine cleanliness, reduced deposits formation, and a superior lubricant for demanding applications.

SPECIFICATIONS

0W-40: API SN/CF • ACEA A3/B3, A3/B4 • MB 229.3 • MB 229.5 • MB 226.5 • PORSCHE A40 • VW 502.00/505.00

5W-30 EURO: API SN/CF • ACEA A3/B3, A3/B4 • MB 229.3 • MB 229.5 • MB 226.5 • RENAULT RN 0700/0710 • VW 502.00/505.00

5W-40 EURO: API SN/CF • ACEA A3/B3, A3/B4 • MB 229.3 • MB 229.5 • MB 226.5 • BMW-LL-01 • PSA B71 2290 • PORSCHE A40 • RENAULT RN 0700/0710 • VW 502.00/505.00

TYPICAL PROPERTIES

PRODUCT CODES			
Product	0W-40	5W-30 EURO	5W-40 EURO
Viscosity, cSt @ 100°C	13.3	11.6	13.2
Viscosity, CCS cP @ -30°C	5700	5780	5800
Phosphorous, Wt. (%)	.095	.095	.095
Zinc, Wt. (%)	.106	.106	.106
Sulfated Ash, % wt.	1.1	1.1	1.1
HTHS cP @150°C	3.6	3.5	3.7
NOACK, Wt. (%)	10.0	10.0	10.0
TBN	10	10	10