

Goodyear Lubricants

420 Imperial Court Bensalem, PA 19020

United States Tel: (215) 244-2114

Fax: (215) 244-2118

www.gylubricants.com



PERFORMANCE MAX UNIVERSAL TRACTOR FLUID

OVERVIEW

Performance Max UNIVERSAL TRACTOR FLUID is a premium, exceptional high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

FEATURES & BENEFITS

Performance Max UNIVERSAL TRACTOR FLUID has enhanced friction properties that optimize clutch and PTO performance, improve PTO chatter control and has excellent clutch and elastomer compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. **Performance Max UNIVERSAL TRACTOR FLUID** has exceptional low temperature, anti-wear, and extreme pressure properties to protect key components.

APPLICATIONS

Performance Max UNIVERSAL TRACTOR FLUID is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. This product is suitable for top-up and re-fill of systems. **Performance Max UNIVERSAL TRACTOR FLUID** is also used for certain commercial transmission applications requiring **Type A** (Suffix A) or **DEXON™ fluids**. Check your manual for your equipment's specific requirements. Do not use in passenger car automatic transmissions.

SPECIFICATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3540, MAT-3525, MAT-3509, MAT-3506, MAT-3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C48-A/B, M2C41-B • International Harvester B-6 Hy-Tran • John Deere J20C (Hy-Gard™), J20A/B, J21A, J14B/C • Kubota UDT/Super UDT Fluids • Massey Ferguson M1145, M1143, M1141 (Permatran III), M1135, M1129A, M1127B, M1110 • Minneapolis-Moline 35301, 35202, 35154 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers I-286-S, 35VQ25, M-2950-S • White Farm Equipment Q-1826 (HTF), Q-1802 (Type 55 Fluid), Q-1766B, Q-1722, Q-1705 • ZF TE-ML 03E/05F/06K/17E/21F

TYPICAL PROPERTIES

PRODUCT CODE	
Viscosity, cSt @ 40°C	54.7
Viscosity, cSt @ 100°C	9.4
Viscosity, cP @ -20°C	4,000
Viscosity, cP @ -40°C	44,500
Viscosity Index	155
Pour Point	-44
Flash Point	432
Sulfated Ash, wt. %	1.48
Zinc, wt. %	.1547